


A1050 (非熱処理系)

A1050TD (引抜)-H ◆…L=2000mm ●…L=4000mm ★…L=5000mm △…取寄 (1070T H14)



外 径 mm	肉厚0.3	1.0	1.5	2.0	3.0	4.0	5.0
3.0	◆						
4.0		●					
5.0		●					
6.0		△					
8.0		△					
9.0							
9.5							
10.0		△	△				
11.0							
12.0		△		△			
12.7		△					
13.0							
14.0		△		△			
15.0		●					
16.0		△	△	△			
18.0		△	△				
19.0		△	△	△	△		
20.0		△	△	△			
22.0		△	△	△			
25.0		△	△	△	△		
28.0				△			
30.0		△		△	△		
32.0		●		●	△		
35.0				△	△		
38.0				△	△		
40.0		△		△	△	△	
42.0				△			
43.0			△				
45.0				△	△		△
50.0			●	△	△	△	△
60.0					△	△	△
65.0					△		△
70.0					△		△
75.0					△		△
76.2					★		
80.0					△		△
85.0							△
90.0					△		△
100.0					△	△	△
101.6					★		
110.0					△		△
120.0					△		△
130.0					△		△
150.0					△		△
165.0							△

*●・◆・★印は在庫がございます。△印は1070T(取寄)になります。


A6063TD (引抜)-H

◆…L=3000mm

●…L=4000mm

★…L=5000mm

△…取寄




外 径 mm	肉厚1.0	1.5	2.0	3.0	5.0	6.0
6.0	●					
8.0	●					
9.0	●					
10.0	●					
11.0	●					
12.0	●					
13.0	●					
14.0	●					
15.0	●					
16.0	●	●				
18.0	●					
19.0	●	●				
20.0	●	●	●			
22.0	●	●	●			
25.0	●	●	●	●		
28.0	●	●	●			
30.0	●	●	●	●		
32.0	●	●	●	●		
35.0	●	●	●	●		
38.0	●	●	●			
40.0	●	●	●	●		
45.0	●	●	●	●		
50.0	●		●	●		
55.0			●	●		
60.0				●		
65.0				★		
70.0				★		
75.0				★		
80.0				★		
90.0				★		
100.0					★	
110.0				★	★	
120.0				★	★	
130.0				★	★	
140.0					★	
150.0					★	
160.0					★	
180.0					●	
200.0					●	
220.0						◆

* ●・◆・★印は在庫がございます。

A6063TE (押出)-T5

●…L=4000mm △…取寄



外 径 mm	肉厚1.0	1.5	2.0	2.5	3.0	4.0	5.0
10.0	●	△	△				
11.0	●						
12.0	●	△	△				
13.0	●	△					
14.0	●	△	△				
15.0	●	△	△				
16.0	●	●	△				
18.0	●	△	△				
19.0	●	●	△				
20.0	●	●	●	△	△		
22.0	●	●	●		●		
25.0	●	●	●	△	●		
28.0	●	●	●		△		
30.0	●	●	●	△	●	△	
32.0	△	●	●		●		
35.0		●	●	△	●	△	
38.0		●	●		△		
40.0		●	●	△	●	●	△
42.0			△				
45.0		●	●		●		△
50.0		●	●	△	●	△	●
55.0			●		●		
60.0			●		●	△	●
65.0			●		●		
70.0			△		●	△	△
75.0					●		
80.0					●	△	●
90.0					●		●
100.0					●		●
110.0					●		●
120.0					●		●
130.0							●
140.0							△
150.0					△		●
160.0							△
180.0							△
200.0							△

A5052TD（引抜きパイプ）

中程度の強度を持った代表的な合金で耐食性・加工性に優れています。

特に強度の割りに疲労強度が強く、耐海水性に優れています。

加工歪みが出にくい材料でもあります。

用途例：印刷機械・フィルムロールなど



外径	肉厚	在庫
42	7	○
52	4	○
52	5	○
52	7	○
60	6	○
62	7	○
72	7	○
77	7	○
77	8	○
78	7	○
82	6	○
82	7	○
82	8	○
87	6	○
89	7	○
92	6	○
92	7	○
92	8	○
100	7	○
102	6	○
102	7	○
102	8	○
102	10	○
104	7	○
112	8	○
117	8	○
120	7	○
122	6	○
122	7	○
122	8	○
122	10	○
127	8	○
132	8	○
142	8	○
150	7	○
152	8	○
152	10	○
162	8	○
173	10	○
183	9	○
203	8,75	○
203	10	○
203	14	○
220	10	○
220	15	○
222	10	○
253	12	○

* ○印の物は在庫がございます。

* 上記在庫品は全てご希望の長さにて切断販売可能です。

* その他サイズも製造可能ですので別途お問い合わせ下さい。